


SUPRAMID

BLACK



Type	Twisted and coated multifilament Sizes 5/0 and 6/0 monofilament
Composition	Polyamide 6.6 strands enclosed in a polyamide 6 sheet
Colour	Black
Tissue reaction	Minimal
Absorption	Non absorbable, gradually encapsulated by connective tissue
Presentation	Box with 12 sutures

*For quality
&
safety*

smi

www.sutures.be

SUPRAMID

BLACK

CHARACTERISTICS

- ✓ High tensile strength, non absorbable
- ✓ Synthetic
- ✓ Twisted structure
- ✓ Multifilament in a sheath
- ✓ Pliability and softness
- ✓ Hermetically sealed packing

INDICATIONS General soft tissue closing
and/or ligation
especially in Skin closure

BENEFITS

Excellent and permanent tissue support

Minimal tissue reaction

Excellent handling properties
High flexibility
High tensile strength
Excellent knot security

Soft passage through the tissues without sawing,
tissue drag and trauma
Good knot tie down / adjustability
Reduced capillary action

Good handling properties
Easy and secure knotting

Guaranteed seal and product sterility

CONTRAINDICATIONS Cardiovascular surgery
Neurosurgery
Microsurgery

 Round bodied taper point		Metric	USP	Length		Order number
1/2 circle 	HR 16 mm		1.5	4/0	75 cm	<i>black</i> 4150116
			2	3/0	75 cm	<i>black</i> 4200116
	HR 20 mm		2	3/0	45 cm	<i>black</i> 4200120
	HR 26 mm		3	2/0	75 cm	<i>black</i> 4300126

 Round bodied taper point		Metric	USP	Length		Order number
Straight 	GR 22 mm		1.5	4/0	50 cm	<i>black</i> 4152022

 Reverse cutting		Metric	USP	Length		Order number
1/2 circle 	HS 17 mm		1.5	4/0	75 cm	<i>black</i> 4151417
			2	3/0	75 cm	<i>black</i> 4201417
	HS 20 mm		1	5/0	75 cm	<i>black</i> 4101420
			1.5	4/0	75 cm	<i>black</i> 4151420
	HS 22 mm		2	3/0	75 cm	<i>black</i> 4201420
			1.5	4/0	75 cm	<i>black</i> 4151422
	HS 26 mm		2	3/0	75 cm	<i>black</i> 4201422
			1.5	4/0	75 cm	<i>black</i> 4151426
	HS 26 mm		2	3/0	75 cm	<i>black</i> 4201426
			3	2/0	75 cm	<i>black</i> 4301426

 Cutting		Metric	USP	Length		Order number
Straight 	GS 20 mm		1.5	4/0	50 cm	<i>black</i> 4152120
	GS 25 mm		1.5	4/0	60 cm	<i>black</i> 4152125

 Reverse cutting		Metric	USP	Length		Order number
3/8 circle 	DS 12 mm		0.7	6/0	75 cm	<i>black</i> 4071512
			1	5/0	45 cm	<i>black</i> 4101512-45
			1	5/0	75 cm	<i>black</i> 4101512
			1.5	4/0	45 cm	<i>black</i> 4151512



Reverse cutting

3/8 circle



		Metric	USP	Length		Order number
DS 16 mm		0.7	6/0	75 cm	black	4071516
		1	5/0	45 cm	black	4101516-45
		1	5/0	75 cm	black	4101516
		1.5	4/0	45 cm	black	4151516
		1.5	4/0	75 cm	black	4151516-75
		2	3/0	45 cm	black	4201516
		2	3/0	75 cm	black	4201516-75
	DS 16 mm black	1	5/0	75 cm	black	4101516VB
	DS 19 mm	0.7	6/0	75 cm	black	4071519
		1	5/0	75 cm	black	4101519
		1.5	4/0	45 cm	black	4151519
		1.5	4/0	75 cm	black	4151519-75
		2	3/0	45 cm	black	4201519-45
		2	3/0	75 cm	black	4201519
		3	2/0	75 cm	black	4301519
	DS 19 mm Easy Pass	1.5	4/0	75 cm	black	4151519P-75
	DS 19 mm black	1	5/0	75 cm	black	4101519VB
		1.5	4/0	75 cm	black	4151519VB
	DS 24 mm	2	3/0	75 cm	black	4201524
		3	2/0	75 cm	black	4301524
		3.5	0	75 cm	black	4351524
	DS 36 mm	3	2/0	75 cm	black	4301536
		3.5	0	75 cm	black	4351536
		4	1	75 cm	black	4401536



Round bodied taper cutting point

1/2 circle



		Metric	USP	Length		Order number
HRT 18 mm		1.5	4/0	75 cm	black	4150518
		2	3/0	75 cm	black	4200518



Round bodied taper cutting point

3/8 circle



		Metric	USP	Length		Order number
DRT 18 mm		1.5	4/0	75 cm	black	4150418
		2	3/0	75 cm	black	4200418